



Introduction

The SoliBoard™ High Temp Series consists of boards which are all designed for a special purpose. Either these boards have been developed for extreme durability, high temperature performance and fit for the most demanding applications. SoliBoard™ High Temp Series are an addition to an extensive board product range targeted to provide solutions in a widest possible range of applications, industries, and atmospheres.

Utilizing our continuous production process with state of the art drying techniques we are able to manufacture a uniform, lightweight, low shot and stable board to a thickness of 100 mm at high consistency, quality and performance.

SoliBoard™ PCW INO-grade

The SoliBoard PCW INO-grade, with a classification temperature of 1600°C, is the top end of our SoliBoard product range. We manufacture our SoliBoard PCW INO from a mixture of poly crystalline fibers and a small percentage of our own developed and heat treated SoliWool HA fiber.

The result is a product which is showing less than 1% shrinkage even if tested at 1600°C. Because the SoliBoard PCW INO-grade is manufactured using special inorganic fillers there is hardly any fumes or loss of strength at first firing.

The SoliBoard High Temp Series are complimented by an extensive range of standard refractory ceramic fiber (RCF), High Strength Boards and low bio persistence (LBP) fiber boards.

Type

Boards from high temperature Poly Crystalline Wool (PCW) and Refractory Ceramic Fiber (RCF) wool and selected fillers.

Temperature range

SoliBoard™ PCW INO-grade has a classification temperature of 1600°C.

The maximum continuous use temperature provided on the datasheet is guideline and only applicable in a clean oxidizing atmosphere.

Typical applications

- Thermal insulation for furnace linings
- Chemical resistant lining in furnaces operating in reducing atmospheres
- Lining combustion chamber for gas fired boilers and heaters
- General technical insulation of furnaces and technical installations

Benefits

- Low shot technology
- Excellent insulation performance
- High handling strength
- Resistant to erosion from high gas velocities
- Can be used in direct flame contact
- Low shrinkage
- Excellent thermal stability
- Resistant to thermal shock



Properties measured	Standard	Unit	SoliBoard PCW INO-grade
Grade			PCW/RCF blend
Colour			white
Classification temperature		°C	1600
Continuous use temperature		°C	1500
Density		kg/m ³	450
Loss on ignition	GB/T6900	wgt%	< 3
Compressive strength	EN ISO8895	kPa	
@ 5% deformation			> 200
@ 10% deformation			> 280
Permanent linear shrinkage	EN 1094-7	%	
@ 1500°C			< 1
Thermal conductivity	ASTM C201	W/mK	
@ 200°C			0,05
@ 400°C			0,07
@ 600°C			0,10
@ 800°C			0,14
@ 1000°C			0,20
@ 1200°C			0,25
Chemical composition (after firing),	GB/T 21114	%	
Al ₂ O ₃			60-62
SiO ₂			37-40
ZrO ₂			-
Other			< 1

Contact

Vulcor Insulation BV
Wanraaij 4
6673 DN Andelst,
The Netherlands
T: +31 (0)488 700 202
E: sales.support@vulcor.com
www.vulcor.com

This information is composed for marketing purposes and is accurate to the best knowledge of Vulcor Insulation BV. All values give are typical values, not guaranteed unless explicitly expressed. As Vulcor Insulation BV and its selected 3rd party partners strive to continually improve our products as means of continues development, properties may be subject to change without notice. Vulcor Insulation BV accepts no legal responsibility for use or reliance upon this data. For information regarding specific applications of the product please contact Vulcor Insulation BV.

The productlabel 'Soli', the company name 'Vulcor' and the 'ULS' technology are registered trademarks of Vulcor Insulation BV.

Availability

SoliBoard High Temp Series is available in a standard size of 1000x600 mm which are supplied on carton boxes of approximately 120mm high (based on the thickness of the board). Please refer to the list below for packaging details of the SoliBoard product range, other sizes are available on request.

SoliBoard High Temp Series 1000x600 mm		
Thickness	Per carton box	Boards per pallet
10	12	336
13	10	280
25	5	140
50	2	72

Product range

SoliBoard is part of an extensive product range supplied by Vulcor Insulation. Vulcor Insulation is supplying insulation solutions from cryogenic to high temperature applications. All products offered by Vulcor are manufactured in house or sourced from exclusive trusted 3rd party partners.

Technical support

Vulcor Insulation provides specifiers and customers with guidance on all aspects of the materials selection for their application, the installation and compliance with relevant regulations and performance standards.

For additional information about product performance or to identify the recommended product for your application, please contact the team at Vulcor Insulation.