



### Introduction

**SoliPaper™ HS is a unique high-strength paper in the SoliPaper product range. It is made from SoliWool™ ULS® fibers along with a small percentage of special high-strength fibers and selected fillers. SoliPaper™ HS offers up to 8 times higher tensile strength than standard low bio persistence fiber paper, delivering exceptional strength, mechanical resistance, a smooth surface, and low dust.**

While SoliPaper HS is primarily based on 2300°F rated SoliWool ULS bulk fiber, it is recommended for continuous use temperatures up to 1832°F due to the burnout of fillers and added high-strength fibers over time.

Manufactured from our Generation III ultra-clean and fine SoliWool ULS bulk fiber, SoliPaper HS has a smooth surface, precise dimensional tolerances, minimal dust, extremely high handling strength, superior thermal insulating performance and retains its flexibility after compression.

SoliPaper HS is an ideal choice for gasket production in domestic appliances and automotive heat shields, originally designed as a fire protection shield for EV battery pack thermal runaway. It combines high strength, low dust, and temperature resistance.

With its flexibility and high tensile strength, SoliPaper HS is targeted for applications requiring further processing such as laminated composites, die-cutting, rolling, and folding.

All products within the SoliWool ULS fiber range, including SoliPaper HS, meet the requirements specified under NOTE Q of European Regulation 1272/2008. Therefore, SoliPaper ULS products are exempt from labeling requirements in Europe.

SoliPaper HS is exclusively available in Jumbo-sized rolls, making it optimal for producing large quantities of die-cut gaskets, minimizing cutting waste in the automotive and domestic appliances industries.

### Type

High Strength paper from low bio persistence (LBP) high temperature insulation fibers and special fillers

### Temperature range

SoliPaper HS has a classification temperature of 1832°F and recommended for use to 1650°F continuously in clean oxidizing atmosphere.

### Typical applications

- Gasket for domestic appliances
- Thermal insulation in automotive heat shields
- Fire protection shield against thermal runaway (EV vehicles)
- General technical insulation of furnaces and technical installations

### Benefits

- High fiber index
- Low shot technology
- Excellent insulation performance
- High handling strength
- Close dimensional tolerance
- Smooth surface and low dust
- Easy die-cutting for high temperature gaskets
- Excellent thermal stability
- Exonerated of carcinogenic classification under Note Q



Properties measured	Standard	Unit	SoliPaper™ HS-grade
Grade			LBP
Colour			white
Classification temperature		°F	1832
Continuous use temperature		°F	1650
Density		PCF	14.5-15.5
Loss on ignition		wgt%	< 10
Tensile strength			
Thickness 1/16 to 1/8"		PSI	> 225
Thickness 1/8" to 1/4"		PSI	> 375
Permanent linear shrinkage	EN 1094-7	%	
@1800°F			< 4
Thermal conductivity	ASTM C201	BTU·in/hr·ft²·°F	
@ 500°F			0.42
@ 1000°F			0.68
@ 1500°F			1.14
Chemical composition (after firing),	ISO 12677	%	
SiO <sub>2</sub>			63-66
Al <sub>2</sub> O <sub>3</sub>			0-2
CaO			25-32
MgO			3-7
Other			< 1,5

### Contact

Vulcor Insulation BV  
Wanraaij 4  
6673 DN Andelst,  
The Netherlands  
T: +31 (0)488 700 202  
E: sales.support@vulcor.com  
[www.vulcor.com](http://www.vulcor.com)

This information is composed for marketing purposes and is accurate to the best knowledge of Vulcor Insulation BV. All values give are typical values, not guaranteed unless explicitly expressed. As Vulcor Insulation BV and its selected 3<sup>rd</sup> party partners strive to continually improve our products as means of continues development, properties may be subject to change without notice. Vulcor Insulation BV accepts no legal responsibility for use or reliance upon this data. For information regarding specific applications of the product please contact Vulcor Insulation BV.

The productlabel 'Soli', the company name 'Vulcor' the product 'NXT' and the 'ULS' technology are registrated trademarks of Vulcor Insulation BV.

### Availability

SoliPaper HS is available in palletized jumbo rolls, with 4 rolls per pallet. The rolls are equipped with hoist belts to ease the unloading process. Please refer to the provided list for the dimensions of the jumbo rolls.

Length (inch)	Width (inch)	Thickness (inch)
9000	47-1/4	1/16
4500	47-1/4	1/8
2250	47-1/4	1/4

### Product range

SoliPaper HS is part of Vulcor Insulation's extensive product range, which offers insulation solutions for a wide range of applications, from cryogenic to high temperature environments. All products supplied by Vulcor are either manufactured in-house or sourced from exclusive trusted third-party partners.

### Technical support

Vulcor Insulation provides technical support to specifiers and customers, offering guidance on material selection, installation, and compliance with relevant regulations and performance standards.

For further information regarding product performance or to find the recommended product for your specific application, please reach out to the Vulcor Insulation team.